






Schematic



Model No.	Switching Position		
R101	ON	NONE	ON
R102	ON	NONE	(ON)
R103	ON	OFF	ON
R104	(ON)	OFF	(ON)
R105	ON	OFF	(ON)
Term Comm.	2-3	OPEN	2-1

SPECIFICATIONS:

CONTACT RATING : 5 AMPS @ 120 V AC or 28 V DC.
 2 AMPS @ 250 V AC or 0.4 AMPS @ 20 V AC or DC.
 ELECTRICAL LIFE : 50,000 make-and-break cycles at full load.
 CONTACT RESISTANCE : 10 mΩ max. initial @ 2-4 V DC.
 100 mA, for both silver and gold plated contacts.
 INSULATION RESISTANCE : 1,000 MΩ min.
 DIELECTRIC STRENGTH : 1,000 V RMS @ sea level.
 OPERATING TEMPERATURE : -30 °C to 130 °C

MATERIALS:

CASE : Diallyl phthalate (DAP)(UL-94V-0).
 ACTUATOR : Nylon, black standard.
 BUSHING : Brass, nickel plated.
 HOUSING : Stainless steel.
 TERMINAL/CONTACT : Brass, with silver or gold plated.
 or gold over silver.
 SWITCH SUPPORT : Brass, tin plated.

SWEETA® 喜威達企業股份有限公司 SWEETA PRODUCTS CORPORATION 23552 新北市中和區中正路799號 TEL:886-2-2226-8001 FAX:886-2-2226-8002 http://www.sweeta.com.tw E-mail : sweeta.tw@msa.hinet.net				TOLERANCE
ITEM NO	R10()R4A1-KK	DATA		.X ± 0.2
CHECKED BY		DRAWN BY		.XX ± 0.05